

IN THE SPECIFICATION:

Please amend the specification of the above-identified application according to the following:

Please delete the paragraph beginning on page 2, line 4.

Please delete the paragraph beginning on page 2, line 5.

Please amend the paragraph beginning on page 2, line 7 as follows.

--FIG. 31 is a cross sectional view of one embodiment of the candle with an ~~insert~~internal cavity therein for ~~providing illumination~~receiving an enclosed insert;--

Please amend the paragraph beginning on page 2, line 9 as follows.

--FIG. 42 is a ~~front side~~cross sectional view of the ~~one-half~~candle of the ~~capsule body~~FIG. 1 including the ~~light~~enclosed insert that is insertable within the candle;--

Please amend the paragraph beginning on page 2, line 11 as follows.

--FIG. 53 is a ~~right side~~cross sectional view of the ~~body~~right side of the enclosed insert of FIG. 42 including a light source;--

Please amend the paragraph beginning on page 2, line 12 as follows.

--FIG. 64 is a ~~back-side~~cross sectional view of the ~~body~~left side of
the enclosed insert of FIG. 42 including a light source, power source and circuit
board;--

Please amend the paragraph beginning on page 2, line 13 as follows.

--FIG. 75 is a ~~left-side~~bottom view of the ~~body~~candle of FIG. 41
including the enclosed insert; and--

Please amend the paragraph beginning on page 2, line 14 as follows.

--FIG. 86 is a ~~bottom~~top view of the ~~body~~light source, power source
and circuit board of FIG. 42;--

Please delete the paragraph beginning on page 2, line 15.

Please delete the paragraph beginning on page 2, line 16.

Please delete the paragraph beginning on page 2, line 17.

Please delete the paragraph beginning on page 2, line 18.

Please delete the paragraph beginning on page 2, line 19.

Please delete the paragraph beginning on page 2, line 20.

Please amend the paragraph beginning on page 2, line 24 as follows:

--The candle of the present invention is indicated generally at 10.

The candle includes a wax body 12 with a hollow cavity 14 therein in which an insert 16 is selectively positionable. The wax body 12 includes a substantially flat bottom surface 17 with the internal cavity 14 extending therefrom. The insert 16 includes a bright light source 20, and a power source 22 with some form of an on-off switch 24.--

Please amend the paragraph beginning on page 3, line 18 as follows.

--This body 30 protects the circuit board and LED, as well as minimizes the transfer of heat from the light to the candle. This minimizes or ~~insulating~~insulatingly protects the candle from melting or other distortion from the internal light source. The body 30 further protects the circuit board, light and battery from the candle melting onto or over these parts where the candle is subject to undesirable external heat such as the sun.--

Please amend the paragraph beginning on page 3, line 24 as follows.

--The candle need not, ~~in~~and desirably does not include a standard burnable wick thereby prohibiting accidental burning of this candle.--

Please amend the paragraph beginning on page 3, line 32 as follows.

--A Seen in FIGs. 2 and 5, the cap 32 with a functional yet inconspicuous handle 38 is preferably positionable within the open bottom end whereby it selectively locks in place due to outwardly extending nubs 40 on the cap interacting with inwardly extending nubs 42 on the surface defining the open bottom end – this allows for a locked and unlocked position depending upon the rotational position of the cap in relation to the open bottom end.--